

Technical Specifications ePapillon 1000W



- 1000W adjustable ultra-high frequency ballast (Range: 600-1150W).
- High density Vega aluminum reflector with only 1% annual depreciation.
- Patented open reflector design increases efficiency to 95%, promoting longer bulb life due to reduced heat buildup.
- Includes: Phillips Green Power Plus 1000W EL HPS (double ended) lamp.
- Highest PAR Output in the industry 2000 micromol/s, Rated 10.000 hours > 95%.
- Driver efficiency > 95%.
- Sealed housing with Gore-Tex ventilation plug allows for extreme air pressure fluctuation.
- Lamp & reflector easily replaceable.
- 3 Year warranty on fixture, 1 year on bulb.

Rated Mains voltage	220V-240V
Voltage range (+/- 10%)	176V-264V
Frequency	50Hz – 60Hz
Current	4,4 A typical @ 240V
Operation frequency (typical)	100 kHz
Rated Power	1060W @ 240V
Inrush current	< 50A
Power factor	>0,95
Dimming type	600W, 660W, 750W, 825W, 1000W, 1150W
Philips GreenPower Plus 1000W EL	>2000 $\mu\text{mol/s}$. Rated 10.000 hours > 95%
Weight	5,4 kg (11.9 lbs.)
Dimensions (lxwxh)	38,0 x 23,0 x 33,0 cm (18.5 x 9.1 x 13.0 inch)
MET Certification E113627	Complies with UL1598 Complies with CAN/CSA C22.2 No. 250.0-08
www.epapillon.com	

